

Wall mounted unit

Wall mounted unit providing high efficiency and comfort

- › Guaranteed heating capacity at low ambient temperature, down to -25°C
- › The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- › Seasonal efficiency values: full range A++ in cooling and heating
- › Voice command via Amazon Alexa or Google Assistant to control main functions such as set point, operation mode, fan speed, etc
- › Daikin residential controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
- › Space saving contemporary wall mounted design
- › Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency



Efficiency data				FTXTP + RXTP	25K+25N8	35K+35N8
Cooling capacity	Min./Nom./Max.			kW	0.70/2.50/4.00	0.70/3.50/4.40
Heating capacity	Min./Nom./Max.			kW	0.80/3.20/6.20	0.80/4.00/6.70
Power input	Cooling	Nom.		kW	0.57	0.92
	Heating	Nom.		kW	0.65	0.90
Space cooling	Energy efficiency class				A++	
	Capacity	Pdesign		kW	2.50	3.50
	SEER				7.10	7.20
	Annual energy consumption			kWh/a	123	170
Space heating (Average climate)	Energy efficiency class				A++	
	Capacity	Pdesign		kW	2.50	3.00
	SCOP/A				4.98	4.81
	Annual energy consumption			kWh/a	703	873
Space heating (Cold climate)	Energy efficiency class				A	
	Capacity	Pdesign		kW	3.70	4.40
	Annual energy consumption			kWh/a	1,939	2,429
	SCOP/C				3.95	3.80
Nominal efficiency	EER				4.40	3.80
	COP				4.95	4.44
	Annual energy consumption			kWh	284	461
	Energy labeling Directive	Cooling/Heating				A/A

Indoor unit				FTXTP	25K	35K
Dimensions	Unit	HeightxWidthxDepth		mm	285x770x225	
Weight	Unit			kg	9.0	
Air filter	Type				Removable / washable	
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m³/min	4.3/5.3/7.7/10.6	4.3/5.4/8.2/11.4
		Heating	Silent operation/ Low/Medium/High	m³/min	4.9/5.8/8.0/11.2	4.9/5.8/7.8/10.8
Sound power level	Cooling			dB(A)	58	
	Heating			dB(A)	58	
Sound pressure level	Cooling	Silent operation/Low/High		dB(A)	21/26/43	
	Heating	Silent operation/Low/High		dB(A)	21/26/43	
Control systems	Infrared remote control				ARC480A11	
	Wired remote control				BRC944B2 / BRC073A1	

Outdoor unit				RXTP	25N8	35N8
Dimensions	Unit	HeightxWidthxDepth		mm	551x763x312	
Weight	Unit			kg	38	
Sound power level	Cooling			dB(A)	61	
	Heating			dB(A)	61	
Sound pressure level	Cooling	Nom.		dB(A)	48	
	Heating	Nom.		dB(A)	49	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~-46	
	Heating	Ambient	Min.~Max.	°CWB	-25~-18	
Refrigerant	Type				R-32	
	GWP				675	
	Charge			kg/TCO2Eq	1.1/-	
Piping connections	Liquid	OD		mm	6.35	
	Gas	OD		mm	9.50	
	Piping length	OU - IU	Max.	m	20	
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)	
Power supply	Level difference		IU - OU	Max.	15	
	Phase/Frequency/Voltage			Hz/V	1~/50/220-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	16	

See separate drawing for electrical data | See separate drawing for operation range | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | Contains fluorinated greenhouse gases